



JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS) MINIMUM
BF22180-28B	x = .346 y = .319	1140 @ 0°C	380	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
B	RATED LIFE HRS MINIMUM	7/30/09	DRAWN BY	APPVD BY	DATE	SIZE	FSCM NO.	DRAWING NO.	BF22180-28B	
A	CIRCUIT & LAMP VOLTAGE CHANGE	7/19/04	L. WENGSTROM	L.R.	7/30/09	A	55335			
RELEASED & CANCEL P-0303-14		9/2/03								
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
						NONE	9/2/03	7/30/09	B	1 OF 1