



USED ON

- ELECTRICAL**
1. RESISTANCE AT 0°C: SEE TABLE, EXCLUDING LEADWIRE RESISTANCE.
  2. RESISTANCE-TEMPERATURE COEFFICIENT: .00385 OHM/OHM/°C (NOMINAL FROM 0°C TO 100°C).
  3. INSULATION RESISTANCE: 1,000 MEGOHMS MINIMUM AT 500 VOLTS D.C., LEADS TO CASE.

- MECHANICAL**
1. ELEMENT: PLATINUM.
  2. LEADWIRE: AWG #24, STRANDED, TEFLON INSULATED, WITH MYLAR FOIL SHIELD AND FEP JACKET OVERALL.
  3. LEAD TERMINATION: WIRE FERRULES.
  4. CASE: STAINLESS STEEL.
  5. TEMPERATURE RANGE: -50°C TO 250°C.

Part Number	Resistance at 0C	Cable Configuration	Y' Cable Length
20009209-00	100 Ohm +/- .06%	3 Wire (RRW)	36.0"
20009209-01	100 Ohm +/- .06%	4 Wire (RRWW)	36.0"
20009209-02	1,000 Ohm +/- .12%	3 Wire (RRW)	36.0"
20009209-03	1,000 Ohm +/- .12%	4 Wire (RRWW)	36.0"

**EAR CONTROLLED**

Technical information subject to the U.S. Export Administration Regulations (EAR). This technical information is prohibited from transfer or disclosure in any manner to non-U.S. persons in the United States or abroad without prior approval by the U.S. Commerce Department or EAR exemption.

This drawing and the information thereon are the property of Measurement Specialties Inc. a TE Connectivity CO. all unauthorized use and reproduction is prohibited.

NO CHANGES TO BE MADE TO THIS DRAWING WITHOUT APPROVAL OF MEAS TPG ANDOVER

REVISION RECORD	P	LTR	DATE	DMN	APVD

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC	± .020
1 PLC	± .010
3 PLC	± .005
4 PLC	± .003

DMN	CHK	APVD	NAME
04.18.19			

Measurement Specialties Inc. a TE Connectivity CO.

**STE** TE Connectivity

RTD, Capsule, Cable, Wire Ferrules

SCALE	SIZE	DRAWING NO	SHEET	OF	REV
NTS	A3	20009209	1	1	A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES (TE). IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TE PERSONNEL, WITHOUT AUTHORIZATION FROM TE (www.TE.com).