



JKL PART NUMBER	- A - LENGTH	COLOR 5000 °k	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
CF26346-37B	346±3.0	x = .345±.01 y = .360±.01	1450	700	6± 1	36,000±15%	40,000
CF26397-37B	397±3.0		1520	725			
CF26448-37B	448±3.0		1820	870			
CF26499-37B	499±3.0		2100	1000			
CF26550-37B	550±3.0		2270	1100			
CF26600-37B	600±3.0		2340	1125			

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		<h1>JKL COMPONENTS CORPORATION</h1>					
		THIRD ANGLE PROJECTION		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
DRAWN BY L. WENGSTROM		APPV'D BY DATE J.K. 11/18/04		SIZE A	FSCM NO. 55335	DRAWING NO. CF 26-37B			
CHANGE LENGTH & PART NO. RELEASE & CANCEL P-0410-05		11/18/04 11/17/04		- CAD DRAWING -					
REV. NO. DESCRIPTION/ECO NUMBER		APPV'D DATE		SCALE NONE		RELEASED DATE 11/17/04	REVISION DATE 11/18/04	REV. NO. A	SHEET 1 OF 1