

## Smart 216 16-Port Multi-User Cat5 KVM Switch for Rack Environments

MODEL NUMBER: 0SU22090



### Description

Multi-user access and control of many computers/servers

Straightforward set up

Space saving devices that eliminate cable clutter

From server rooms to data centers

### Features

- 16 Ports with 2 simultaneous KVM Users
- BIOS level access
- USB keyboard and mouse console
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

## Specifications

### Highlights

- 16 Ports with 2 simultaneous KVM Users
- BIOS level access
- USB keyboard and mouse console
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

### System Requirements

#### Operating System

- Windows, Novell, Linux, SUN Solaris

#### Resolution

- Supports video resolutions up to 1600 x 1200 @ 85Hz

#### Package Includes

- Smart 216
- Power Cord
- RS232 Cable
- Rackmount Hardware
- Owner's Manual

| <b>OVERVIEW</b>                      |                            |
|--------------------------------------|----------------------------|
| UPC Code                             | 654518209914               |
| <b>PHYSICAL</b>                      |                            |
| Color                                | Black                      |
| Shipping Dimensions (hwd / in.)      | 5.30 x 13.00 x 19.80       |
| Shipping Dimensions (hwd / cm)       | 13.46 x 33.02 x 50.29      |
| Shipping Weight (lbs.)               | 7.20                       |
| Shipping Weight (kg)                 | 3.27                       |
| Unit Dimensions (hwd / in.)          | 1.700 x 17.000 x 10.600    |
| Unit Dimensions (hwd / cm)           | 4.4 x 43.1 x 27            |
| Unit Weight (lbs.)                   | 5.1                        |
| Unit Weight (kg)                     | 2.31                       |
| <b>ENVIRONMENTAL</b>                 |                            |
| Storage Temperature Range            | -40 to 70 C / -40 to 158 F |
| Relative Humidity                    | 80% Non-Condensing         |
| Operating Temperature                | 0 to 40 C / 32 to 104 F    |
| <b>COMMUNICATIONS</b>                |                            |
| Port Control                         | Hotkeys, OSD               |
| IP Remote Access                     | Yes                        |
| <b>CONNECTIONS</b>                   |                            |
| Number of Ports                      | 16                         |
| Computer/Server Ports                | 16                         |
| PC/Server Connections                | VGA; USB; PS/2             |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                            |
| Cat5 KVM Switch                      | Yes                        |
| NIAP-Certified Secure                | No                         |
| Number of Users                      | 2                          |
| <b>WARRANTY &amp; SUPPORT</b>        |                            |
| Product Warranty Period (Worldwide)  | 3-year limited warranty    |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.